

The VISADES ECOPLUS systems are tested according to common drinking water approvals. These are characterized by the efficiently designed control unit. All important functions for reliable and standard-compliant disinfection of drinking water in private and public areas are provided.

GENERAL	
Manufacturer	VISADES
ÖVGW Certificate	W1.784
DVGW Certificate	----
SVGW Certificate	----
Model	
Number of lamps	1
Flow range	2,83 - 8,30 m³/h
Minimum UV transmission	5% T100mm / 74,11% T10mm
Chamber material	V4A / SS316L
Operating pressure (bar)	PN10/16
Connection	6/4" AG
Control Unit	
Display	4,3" Touch-Display
Mains connection	230VAC/50Hz
Total power (W)	92
Supply line protection (A)	13
Control cabinet protection (A)	6
Protection class	IP54
Compatible with the FlexFlow Control Unit	
Model	VISADES Control Unit FlexFlow IQ40
Standard flushing variant 1	6/4" Solenoid Valve
Flow control (main valve)	6/4" Ball Valve with spring return
Flow measurement	FD-Q32C
UV-Lamp	
Lamp type	ST80-1
Power (W)	88
UVC power (W)	44

UV-Unit Includes:
Functionality

- Stainless steel irradiation chamber V4A/SS316L
- Immersion tube made of high-quality quartz glass
- Powerful low-pressure UVC lamp
- UVC sensor according to ÖNORM M5873-1 for monitoring irradiance
- Electronic ballast with low energy consumption
- Control unit in a powder-coated steel housing IP 54
- Display for system status and irradiation
- Connections for sampling taps, venting/draining

- Clear menu navigation
- FlexFlow IQ flow control mode
- Turbidity monitoring
- Tank level control
- Pressure/temperature monitoring
- Optional SMS communication
- Alarm log



Bereichsname xxx_DVGW_QMAX	T80F_DVGW_QMAX
Bereichsname xxx_OVGW_QMAX	T80F_OVGW_QMAX
Allgemeine, Sverw	5
Allgemeine, Sverw	4
Allgemeine, Sverw	4

4-1
4-4a
4-6a

1-1
1-26
1-27
1-9
1-10
1-14

1-28
3-3
3-4
3-5
3-6
3-7

1-29a
9-4a
9-7a
9-9

1-2
1-3
1-4

